






















ça correspond...

	couple de contrôle	Vis métriques						
		à tête cylindrique	avec guidage	à tête cylindrique	à tête fraisée	vis sans tête		
								
DIN ISO 351-3:2015-08 Nm		ISO 4762	DIN 6912	DIN 7984		ISO 4026 ISO 4029	ISO 4027	ISO 4028
		M	M	M	M	M	M	M
0.7						1.4 1.6 1.8	1.4 1.6 1.8	1.4 1.6 1.8
0.9						2	2	2
1.3		1.4				2.5	2.5	2.5
1.5	1.0	1.6-2				3	3	3
2	2.2	2.5		3	3	4	4	4
2.5	4.4	3		4	4	5	5	5
3	7.7	4	4	5	5	6	6	6
4	19	5	5	6	6	8	8	8
5	35	6	6	8	8	10	10	10
6	60	8	8		10	12 14	12 14	12 14
7	93			10				
8	139	10	10	12	12	16	16	16
10	255	12	12	14	14	18 20	18 20	18 20
12	429	14	14	16 18	18 20	22 24	22 24	22 24

	couple de contrôle	Vis métriques						Vis à tête		
		à tête cylindrique	à tête fraisée	à tête fraisée bombée	à tête cylindrique	à tête bombée à tête aplatie	à tête fraisée	à tête bombée	à tête fraisée	à tête fraisée bombée
										
TORX®	mm Nm				DIN 7984 6912					
grandeur		M	M	M	M	M	M	B	B	B
T5	1.42 0.51	*	*	*	*	*	*	*	*	*
T6	1.70 0.9	*	2	*	*	*	*	*	2.2	*
T7	1.99 1.7	*	*	*	*	*	*	*	*	*
T8	2.31 2.6	2.5	2.5	2.5		2.5		2.9	2.9	2.9
T9	2.50 3.4									
T10	2.74 4.5	3	3	3	3	3		3.5	3.5	3.5
T15	3.27 7.7		3.5	3.5		3.5		3.9	3.9	3.9
T20	3.86 12.7	4	4	4	4	4		4.2	4.2	4.2
T25	4.43 19.0	5	5	5	5	5		4.8 5.5	4.8 5.5	4.8 5.5
T27	4.99 22.5	**	**	**	**	**	**	**	**	**
T30	5.52 37.4	6	6	6	6	6		6.3	6.3	6.3
T40	6.65 65.1		8			8				8
T45	7.82 104	8	**	8	8	8	**	**	**	**
T50	8.83 159	10	10	10	10	10				
T55	11.22 257	12			12					
T60	13.25 446	14			14					

* Vis spéciaux M1.6 et 2.06 pour plaquettes amovibles en métal dur

** is spéciaux