















ça correspond...

		Vis métriques						Vis à tôle			
		à tête cylindrique	à tête fraisée	à tête fraisée bombée	à tête cylindrique	à tête bombée à tête aplatie	à tête fraisée	à tête bombée	à tête fraisée	à tête fraisée bombée	
											
TORX®	mm	Nm				DIN 7984 6912					
Grandeur			M	M	M	M	M	M	B	B	B
T5	1.42	0.43	*	*	*	*	*	*	*	*	*
T6	1.70	0.75	2	*	2	*	2	*	2.2	2.2	2.2
T7	1.99	1.4	*	*	*	*	*	*	*	*	*
T8	2.31	2.2	2.5	2.5	2.5		2.5		2.9	2.9	
T9	2.50	2.8									
T10	2.74	3.7	3	3	3	3	3	3.5	3.5	3.5	3.5
T15	3.27	6.4		3.5	3.5		3.5	4	3.9	3.9	3.5
T20	3.86	10.5	4	4	4	4	4	5	4.2	4.2	4.2
T25	4.43	15.9	5	5	5		5	6	4.8 5.5	4.8 5.5	4.8 5.5
T27	4.99	22.5	**	**	**	**	**	**	**	**	**
T30	5.52	31.1	6	6	6	6	6		6.3	6.3	6.3
T40	6.65	54.1		8				8			8
T45	7.82	86	8	**	8	8	8	**	**	**	**
T50	8.83	132	10	10	10	10	10	10			9.5
T55	11.22	218	12				12				
T60	13.25	379	14				14				

\*Vis spéciaux M1.6 et 2.06 pour plaquettes amovibles en métal dur

\*\*Vis spéciaux