

ça correspond...

		Vis métriques							
			couple de contrôle						
			à tête cylindrique	avec guidage	à tête cylindrique	à tête fraisée	vis sans tête		
									
									
DIN 911 Nm	ISO 4762	DIN 912	DIN 6912	DIN 7984	DIN 7991	ISO 4026 4029	ISO 4027	ISO 4028	
DIN 913 916	DIN 914	DIN 915							
		M	M	M	M	M	M	M	
0.7	0.08					1.4 1.6 1.8	1.4 1.6 1.8	1.4 1.6 1.8	
0.9	0.18					2	2	2	
1.3	0.53	1.4				2.5	2.5	2.5	
1.5	0.82	1.6-2				3	3	3	
2	1.9	2.5		3	3	4	4	4	
2.5	3.8	3		4	4	5	5	5	
3	6.6	4	4	5	5	6	6	6	
4	16	5	5	6	6	8	8	8	
5	30	6	6	8	8	10	10	10	
6	52	8	8		10	12 14	12 14	12 14	
7	78			10					
8	120	10	10	12	12	16	16	16	
10	220	12	12	14	14 16	18 20	18 20	18 20	
12	370	14	14	16 18	18 20	22 24	22 24	22 24	
14	590	16 18	16 18	20 22	22 24				
17	1000	20 22	20 22	24					
19	1000	24 27	24 27						
22	1000	30	30						
24	1000	33	33						
27	1000	36	36						
32	1000	42							