

ça correspond...

		Vis métriques						
		couple de contrôle						
		à tête cylindrique	avec guidage	à tête cylindrique	à tête fraisée	vis sans tête		
								
								
	ISO 4762				ISO 4026 4029	ISO 4027	ISO 4028	
DIN 911 Nm	DIN 912	DIN 6912	DIN 7984	DIN 7991	DIN 913 916	DIN 914	DIN 915	
		M	M	M	M	M	M	
0.7					1.4 1.6 1.8	1.4 1.6 1.8	1.4 1.6 1.8	
0.9					2	2	2	
1.3		1.4			2.5	2.5	2.5	
1.5	0.95	1.6-2			3	3	3	
2	2.3	2.5		3	4	4	4	
2.5	4.4	3		4	5	5	5	
3	7.6	4	4	5	6	6	6	
4	18	5	5	6	8	8	8	
5	35	6	6	8	10	10	10	
6	61	8	8		10 12 14	10 12 14	10 12 14	
7	97			10				
8	140	10	10	12	12	16	16	
10	280	12	12	14	14 16	18 20	18 20	
12	480	14	14	16 18	18 20 24	22 24	22 24	

		couple de contrôle	Vis métriques						Vis à tôle		
			à tête cylindrique	à tête fraisée	à tête fraisée bombée	à tête cylindrique	à tête bombée à tête aplatie	à tête fraisée	à tête bombée	à tête fraisée	à tête fraisée bombée
											
											
			DIN 912	DIN 963 965	DIN 964 966	DIN 7984 6912	DIN 7985	DIN 7991	DIN 7981	DIN 7972 7982	DIN 7973 7983
TORX® grandeur	mm	Nm	M	M	M	M	M	M	B	B	B
T5	1.42	0.51	*	*	*	*	*	*	*	*	*
T6	1.70	0.9	*	2	*	*	*	*	*	2.2	*
T7	1.99	1.7	*	*	*	*	*	*	*	*	*
T8	2.31	2.6	2.5	2.5	2.5		2.5		2.9	2.9	2.9
T9	2.50	3.4									
T10	2.74	4.5	3	3	3	3	3	3	3.5	3.5	3.5
T15	3.27	7.7		3.5	3.5		3.5		3.9	3.9	3.9
T20	3.86	12.7	4	4	4	4	4	4	4.2	4.2	4.2
T25	4.43	19.0	5	5	5	5	5	5	4.8 5.5	4.8 5.5	4.8 5.5
T27	4.99	22.5	**	**	**	**	**	**	**	**	**
T30	5.52	37.4	6	6	6	6	6	6	6.3	6.3	6.3
T40	6.65	65.1		8				8			8
T45	7.82	104	8	**	8	8	8	**	**	**	**
T50	8.83	159	10	10	10	10	10	10			
T55	11.22	257	12			12					
T60	13.25	446	14			14					

* Vis spéciaux M1.6 et 2.06 pour plaquettes amovibles en métal dur

** is spéciaux